

HDX 35C

Technical specifications



GENERAL

Item code	20072000
Type	HDX 35C - Stand alone
Designed use	Add-on for autonomous mobile robots, and/or as a stationary workplace - lifting pallets and other loads of up to 1200 kg.
Colour	Matt black RAL 9005

DIMENSIONS

Lenght	1324 mm +/- 3,0 mm (E-stop adds 32 mm. to both ends)
Width	884 mm +/- 2,0 mm
Height	90 mm +/- 3,5 mm
Height when lifted	150 mm +/- 5,0 mm
Weight (Set)	115 kg.
Standard interface set-up	None

POWER

Voltage	48 V/24 V both required
Operating current/no load	6 A
Operating current/full load	20 A

ENVIRONMENT

Duty cycle full load	Max. 15%
Ambient temperature	-25° to +40°C
Storage temperature	-25° to +70°C
Humidity	10-95% non-condensing
Operating environment	Indoor use only

SAFETY

Closed Cabinet	Yes
Overload protection	Yes
Ingress protection	IP52
SLS switch	Optional
Integrated emergency stop	Yes

TEST AND PERFORMANCE

Life cycle test - no maintenance	60.000 Cycles
Completed life cycle test with maintenance	120.000 Cycles
CoG displacement full load	150 mm
Drop test - no load	500 mm

INPUT/OUTPUT

Power connection	Flying leads
GPIO	Flying leads
Emergency stop	Flying leads
SLS switch	Optional
Payload detection	Optional

ADD-ON

Slide stop	No
Light indicator	No
Tool mounting points	No

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE OR OBLIGATION, TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE. NO LIABILITY IS ACCEPTED.